# **PANZERI**

## Gonio

120-277V AC dimmable (0-10V)

A019U01.060.4653





#### Spec sheet

| CODE                     | A019U01.060.4653    |
|--------------------------|---------------------|
| SYSTEM POWER CONSUMPTION | 45W                 |
| EFFICACY                 | 96.38lm/W           |
| LIGHT SOURCE             | LED                 |
| LIGHT SOURCE LIFETIME    | L70 (B50) 72.000h   |
| COLOUR TEMPERATURE       | 3500K Ra>90         |
| LIGHT DISTRIBUTION       | asymmetric          |
| POWER SUPPLY             | 120-277V AC         |
| FREQUENCY                | 60Hz                |
| ELECTRICAL CONFIGURATION | dimmable (0-10V)    |
| DRIVER                   | integrated included |
| NOMINAL LUMINOUS FLUX    | 6240lm              |
| DELIVERED LUMEN OUTPUT   | 4337lm              |
| EFFICIENCY               | 69.5%               |
| WEIGHT                   | 4,52 lbs            |
| PROTECTION DEGREE        | IP40                |
| COLOUR TOLLERANCES       | SDCM 3              |
| PACKING DIMENSIONS       | 4,9 x 24,8 x 4,9 in |
| -                        |                     |



Wall lighting fixture for interiors, with direct and indirect light emission.

Pickled sheet metal wall bracket in polyacrylic paint.

Extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.


 ${\sf Extruded\ acrylic\ diffusers\ with\ opaline\ finish.}$ 

Die-cast aluminium end caps in polyacrylic paint.






#### **Technical drawing**



### Polar diagram



cd/klm C0 - C180 - - - C90 - C270