PANZERI

Gonio

120V AC 120V-277V dimmable (0-10V)

A019U17.030.0553





Spec sheet

CODE	A019U17.030.0553
SYSTEM POWER CONSUMPTION	24W
EFFICACY	90.33lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 72.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	asymmetric
POWER SUPPLY	120V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	120V-277V dimmable (0-10V)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3120lm
DELIVERED LUMEN OUTPUT	2168lm
EFFICIENCY	69.5%
WEIGHT	1,08 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	19,5 x 35,0 x 10,0 cm

Wall lighting fixture for interiors, with direct and indirect light emission. Pickled sheet metal wall bracket in polyacrylic paint.

Extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.


Extruded acrylic diffusers with opaline finish. Die-cast aluminium end caps in polyacrylic paint.



Technical drawing



Polar diagram



cd/klm C0 - C180 - - - C90 - C270