PANZERI

Gonio

120V AC dimmable (0-10V) A019U17.060.0453

Spec sheet

CODE	A019U17.060.0453
SYSTEM POWER CONSUMPTION	45W
EFFICACY	96.38lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 72.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	asymmetric
POWER SUPPLY	120V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (0-10V)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	6240lm
DELIVERED LUMEN OUTPUT	4337lm
EFFICIENCY	69.5%
WEIGHT	4,52 lbs
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	4,9 x 24,8 x 5,5 in



Wall lighting fixture for interiors, with direct and indirect light emission. Pickled sheet metal wall bracket in polyacrylic paint. Extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint. Extruded acrylic diffusers with opaline finish.

Die-cast aluminium end caps in polyacrylic paint.




Technical drawing



Polar diagram

bronze



<u>cd/klm</u> _____C0 - C180 _ - - - C90 - C270