

# PANZERI

## Gonio

120V AC 120V-277V dimmable (0-10V)

A019U30.060.0553

titanium



### Spec sheet

CODE	A019U30.060.0553
SYSTEM POWER CONSUMPTION	45W
EFFICACY	96.38lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 72.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	asymmetric
POWER SUPPLY	120V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	120V-277V dimmable (0-10V)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	6240lm
DELIVERED LUMEN OUTPUT	4337lm
EFFICIENCY	69.5%
WEIGHT	2,05 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	12,5 x 63,0 x 12,5 cm



Wall lighting fixture for interiors, with direct and indirect light emission.  
Pickled sheet metal wall bracket in polyacrylic paint.  
Extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.  
Extruded acrylic diffusers with opaline finish.  
Die-cast aluminium end caps in polyacrylic paint.

### Technical drawing



### Polar diagram

