


PANZERI

Hilow

120V AC dimmable (0-10V)


A029U19.115.0553

 mat brass




Spec sheet

CODE	A029U19.115.0553
SYSTEM POWER CONSUMPTION	77W
EFFICACY	49.5lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B10) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	120V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (0-10V)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	8064lm
DELIVERED LUMEN OUTPUT	3812lm
EFFICIENCY	47.3%
WEIGHT	6,55 lbs
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	34,3 x 46,5 x 5,5 in



Wall lighting fixture for interiors, with direct and indirect light emission.
 Pickled sheet metal wall bracket in polyacrylic paint.
 Pickled sheet metal wall plate in polyacrylic paint.
 Extruded aluminium structure in white, mat black, bronze, mat brass or titanium polyacrylic paint.
 Joints in turned brass and die-cast aluminium in polyacrylic paint.
 Die-cast aluminium end caps in polyacrylic paint.
 Extruded polycarbonate diffusers with black finish for direct light emission and opaline finish for indirect light emission.

Technical drawing



Polar diagram

