

PANZERI

Zero Line

120V AC 120V-277V ON-OFF

A036U21.100.0551

 gold leaf



Spec sheet

CODE	A036U21.100.0551
SYSTEM POWER CONSUMPTION	22,2W
EFFICACY	58,18lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	120V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	120V-277V ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2896lm
DELIVERED LUMEN OUTPUT	1280lm
EFFICIENCY	44,2%
WEIGHT	1,58 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	10,0 x 105,0 x 5,0 cm



Ceiling or wall lighting fixture for interiors, with direct and indirect light emission. Pickled sheet metal structure in white, bronze or mat brass polyacrylic paint, or with gold leaf coating, or in polished stainless steel. Specular aluminium reflector. Cover in brass with white, bronze or mat brass polyacrylic paint, or with gold leaf coating, or with galvanic chrome plating. Extruded polycarbonate diffuser with opaline finish.

Technical drawing

Application

