# PANZERI

# Bella


120V AC dimmable A052U19.011.0509

### Spec sheet

CODE	A052U19.011.0509
SYSTEM POWER CONSUMPTION	6,5W
EFFICACY	64.67lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	adjustable
POWER SUPPLY	120V AC
FREQUENCY	60Hz
ELECTRICAL CONFIGURATION	dimmable
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	460lm
DELIVERED LUMEN OUTPUT	388lm
EFFICIENCY	84.3%
WEIGHT	1,22 lbs
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	4,7 x 9,5 x 5,1 in



# Technical drawing





mat brass





Ceiling or wall lighting fixture for interiors, with swivelling light beam. Galvanized sheet metal ceiling or wall bracket. Die-cast aluminium wall plate in white, black, bronze, mat brass or titanium polyacrylic paint. Turned brass joints in polyacrylic paint. Die-cast aluminium structure in polyacrylic paint. Die-cast aluminium head rotating on three axes in polyacrylic paint. Modelled acrylic diffuser with mat finish.

Aluminium closing disk in polyacrylic paint.

Push-button to adjust luminosity according to 5 levels of visual comfort.

## Application



#### Polar diagram

