PANZERI

Tubino

120V AC 120V ON-OFF

A073U01.001.0550





Spec sheet

CODE	A073U01.001.0550
SYSTEM POWER CONSUMPTION	6,5W
EFFICACY	56.5lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 80.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	adjustable
POWER SUPPLY	120V AC
FREQUENCY	60Hz
ELECTRICAL CONFIGURATION	120V ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	475lm
DELIVERED LUMEN OUTPUT	339lm
EFFICIENCY	71.4%
WEIGHT	1,37 lbs
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	11,4 x 9,5 x 5,5 in



Ceiling or wall lighting fixture for interiors, with swivelling light beam.

Galvanized sheet metal ceiling or wall bracket.

Die-cast aluminium wall plate in white, champagne, mat black, bronze or titanium polyacrylic paint.

Turned brass joints in polyacrylic paint.

Turned aluminium structure in polyacrylic paint.

Turned aluminium head rotating on two axes in polyacrylic paint.


Modelled polycarbonate diffuser with opaline finish.

Turned brass end cap in polyacrylic paint.





Technical drawing








Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270