# PANZERI

## Hilow Line

120-277V AC dimmable (0-10V) A110U01.100.0553

### white



#### Spec sheet

CODE	A110U01.100.0553
SYSTEM POWER CONSUMPTION	17W
EFFICACY	59.88lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B10) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	120-277V AC
FREQUENCY	60Hz
ELECTRICAL CONFIGURATION	dimmable (0-10V)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1512lm
DELIVERED LUMEN OUTPUT	1018lm
EFFICIENCY	67.3%
WEIGHT	2,56 lbs
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	4,7 x 41,7 x 2,8 in




Wall lighting fixture for interiors, with indirect light emission. Pickled sheet metal wall bracket in polyacrylic paint. Pickled sheet metal wall plate in polyacrylic paint. Extruded aluminium structure in white, mat black, bronze, mat brass or titanium polyacrylic paint. Die-cast aluminium end caps in polyacrylic paint.

Extruded polycarbonate diffuser with opaline finish.



#### **Technical drawing**



#### Polar diagram

