PANZERI

Bella

120V AC 120V dimmable (Step DIM)

C052U17.011.0558





Spec sheet

CODE	C052U17.011.0558
SYSTEM POWER CONSUMPTION	5W
EFFICACY	77.6lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	adjustable
POWER SUPPLY	120V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	120V dimmable (Step DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	460lm
DELIVERED LUMEN OUTPUT	388lm
EFFICIENCY	84.3%
WEIGHT	0,88 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	17,0 x 40,0 x 16,0 cm

Table lighting fixture for interiors, with swivelling light beam.

Pickled sheet metal bearing base in polyacrylic paint.

Body in tapered steel tube in white, black, bronze, mat brass or titanium polyacrylic paint.

Turned brass joint in polyacrylic paint.

Die-cast aluminium structure in polyacrylic paint.

Die-cast aluminium swivelling head in polyacrylic paint.

Modelled acrylic diffuser with mat finish.

Aluminium closing disk in polyacrylic paint.


Push-button to adjust luminosity according to 5 levels of visual comfort.


Equipped with a 1,4m (55,1") long power cable with jack connector and adapter plug.


X




Technical drawing







Polar diagram



<u>cd/klm</u> _____ co - c180 _ - - - c90 - c270