PANZERI

Tubino

120V AC dimmable (Step DIM)





Spec sheet

CODE	C073U05.001.0509
SYSTEM POWER CONSUMPTION	6,5W
EFFICACY	56.5lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 80.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	adjustable
POWER SUPPLY	120V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (Step DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	475lm
DELIVERED LUMEN OUTPUT	339lm
EFFICIENCY	71.4%
WEIGHT	1,42 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	10,5 x 60,0 x 15,0 cm

Table lighting fixture for interiors, with swivelling light beam. Die-cast aluminium bearing base in polyacrylic paint.

Body in steel tube in white or mat black polyacrylic paint.

Turned brass joint in polyacrylic paint.

Turned aluminium structure in polyacrylic paint.

Turned aluminium swivelling head in polyacrylic paint. $\label{thm:modelled} \mbox{Modelled polycarbonate diffuser with opaline finish.}$

Turned brass end cap in polyacrylic paint.


Equipped with connection cable between the head and the body in transparent PVC. Equipped with a 1,4m (55,1") long power cable in transparent PVC with switch and plug.







Technical drawing







Polar diagram

