PANZERI

Bella

120V AC 120V ON-OFF

L 052U01 011 0550





Spec sheet

-	
CODE	L052U01.011.0550
SYSTEM POWER CONSUMPTION	6,5W
EFFICACY	64.67lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	120V AC
FREQUENCY	60Hz
ELECTRICAL CONFIGURATION	120V ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	460lm
DELIVERED LUMEN OUTPUT	388lm
EFFICIENCY	84.3%
WEIGHT	1,20 lbs
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	5,1 x 9,5 x 4,7 in



Pendant lighting fixture for interiors, with direct light emission.

Die-cast aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.


Modelled acrylic diffuser with mat finish.

Aluminium closing disk in polyacrylic paint.






Technical drawing





Polar diagram



cd/klm C0 - C180 - - - C90 - C270