PANZERI

Bella


120V AC 120V ON-OFF L052U17.011.0550


Spec sheet

CODE	L052U17.011.0550
SYSTEM POWER CONSUMPTION	6,5W
EFFICACY	64.67lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	120V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	120V ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	460lm
DELIVERED LUMEN OUTPUT	388lm
EFFICIENCY	84.3%
WEIGHT	0,55 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	13,0 x 24,0 x 12,0 cm



Technical drawing





bronze



Suspension lighting fixture for interiors, with direct light emission. Die-cast aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.

Modelled acrylic diffuser with mat finish.

Aluminium closing disk in polyacrylic paint.

Suspension kit with rod in brass tube in polyacrylic paint.

3m (118,1") long suspension and coaxial power cable in transparent PVC. Power canopy with pickled sheet metal ceiling bracket and extruded aluminium covering in white, black, bronze, mat brass or titanium polyacrylic paint.

Polar diagram

