PANZERI

Tubino

120V AC 120V ON-OFF

L073U06.001.0550





Spec sheet

CODE	L073U06.001.0550
SYSTEM POWER CONSUMPTION	6,5W
EFFICACY	56.5lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 80.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	120V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	120V ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	475lm
DELIVERED LUMEN OUTPUT	339lm
EFFICIENCY	71.4%
WEIGHT	0,51 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	12,0 x 24,0 x 13,0 cm

Suspension lighting fixture for interiors, with direct light emission.

 $\label{thm:champagne} Turned a luminium structure in white, champagne, mat black, bronze or titanium polyacrylic paint.$

Turned aluminium head in polyacrylic paint.

Modelled polycarbonate diffuser with opaline finish.


Turned brass end cap in polyacrylic paint.

2,9m (114,2") long suspension and power cable in transparent PVC.

Power canopy with pickled sheet metal ceiling bracket and extruded aluminium covering in white, champagne, mat black, bronze or titanium polyacrylic paint.




Technical drawing





Polar diagram



<u>cd/klm</u> _____ co - c180 __ - _ - c90 - c270