PANZERI

Dip


120V AC 120V-277V dimmable (0-10V) L084U06.000.0553

Spec sheet

CODE	L084U06.000.0553
SYSTEM POWER CONSUMPTION	18W
EFFICACY	107.28lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	120V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	120V-277V dimmable (0-10V)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3013lm
DELIVERED LUMEN OUTPUT	1931lm
EFFICIENCY	64.1%
WEIGHT	1,98 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	27,0 x 27,0 x 56,0 cm



Technical drawing







Suspension lighting fixture for ceiling installation for interiors, with direct light emission.

Power supply canopy with pickled sheet metal fixing bracket, deep-drawn sheet metal closing frame in polyacrylic paint.

Die-cast aluminum emitting head with polyacrylic paint in champagne, mat black, bronze and soft textured white finishes.

UV technology screen-printed diffuser, made of opal polycarbonate, installed with magnetic coupling.

Suspension kit with painted brass tube tige, power supplay and 3m (118.1") long suspension adjustable coaxial cable.

Polar diagram

