PANZERI

To-be

24V DC

M025U19.085.4610





Spec sheet

CODE	M025U19.085.4610
SYSTEM POWER CONSUMPTION	2,8W
EFFICACY	90.5lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	3500K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	270lm
DELIVERED LUMEN OUTPUT	181lm
EFFICIENCY	67%
WEIGHT	1,41 lbs
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	2,0 x 41,3 x 3,9 in





Multiple suspension lighting fixture for interiors, with direct light emission.

 $\label{thm:continuity} \textbf{Extruded aluminium structure in white, mat black, bronze or mat brass polyacrylic paint or with gold leaf coating.}$

Extruded aluminium heat sink.


Modelled polycarbonate diffuser with opaline finish.

Turned brass end cap in polyacrylic paint.


5 m (196,9") long suspension and power cable in transparent PVC.

Provided without power canopy, complete with cable clamp on the cable's free extremity.

Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270