PANZERI

Zero Square

24V DC 24V M152U02.075.0410

Spec sheet

| CODE | M152U02.075.0410 |
|--------------------------|----------------------|
| SYSTEM POWER CONSUMPTION | 36W |
| EFFICACY | 84.97lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L70 (B50) 60.000h |
| COLOUR TEMPERATURE | 3000K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 24V DC |
| ELECTRICAL CONFIGURATION | 24V |
| DRIVER | remote not included |
| NOMINAL LUMINOUS FLUX | 4252lm |
| DELIVERED LUMEN OUTPUT | 3059lm |
| EFFICIENCY | 71.9% |
| WEIGHT | 2,66 lbs |
| PROTECTION DEGREE | IP20 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS | 32,7 x 32,7 x 3,9 in |








Single or multiple pendant lighting fixture for interiors, with direct and indirect light emission. $% \left({{{\left[{{{\rm{c}}} \right]}}_{{\rm{c}}}}_{{\rm{c}}}} \right)$

Bended extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.

Extruded polycarbonate diffuser with opaline finish



Technical drawing



Polar diagram

