

# PANZERI

## Zero Round

24V DC 24V

M153U01.050.0410

● white



### Spec sheet

CODE	M153U01.050.0410
SYSTEM POWER CONSUMPTION	17W
EFFICACY	119.94lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
ELECTRICAL CONFIGURATION	24V
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	2396lm
DELIVERED LUMEN OUTPUT	2039lm
EFFICIENCY	85.1%
WEIGHT	1,83 lbs
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	53,2 x 53,2 x 24,4 in




Single or multiple pendant lighting fixture for interiors, with direct and indirect light emission.

Bended extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.


Extruded polycarbonate diffuser with opaline finish



### Technical drawing



### Polar diagram



cd/klm  
— C0 - C180    - - - C90 - C270