PANZERI

Zero Round

24V DC 24V M153U17.100.0410

Spec sheet

CODE	M153U17.100.0410
SYSTEM POWER CONSUMPTION	47W
EFFICACY	86.79lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
ELECTRICAL CONFIGURATION	24V
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	5670lm
DELIVERED LUMEN OUTPUT	4079lm
EFFICIENCY	71.9%
WEIGHT	1,43 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	127,0 x 127,0 x 54,0 cm



Technical drawing

bronze



Single or multiple suspension lighting fixture for interiors, with direct and indirect light emission. $% \left({{{\left[{{{\rm{s}}_{\rm{c}}} \right]}}} \right)$

Bended extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.

Extruded polycarbonate diffuser with opaline finish. Suspension kit with griplocks and 5m (196,9") long steel cables. 5m (196,9") long power cable in transparent PVC. Provided without power canopy.

Polar diagram

