PANZERI

Hilow

120-277V AC dimmable (0-10V)

P028U01.115.0553

white



Spec sheet

CODE	P028U01.115.0553
SYSTEM POWER CONSUMPTION	78W
EFFICACY	59lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B10) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	120-277V AC
FREQUENCY	60Hz
ELECTRICAL CONFIGURATION	dimmable (0-10V)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	8316lm
DELIVERED LUMEN OUTPUT	4602lm
EFFICIENCY	55.3%
WEIGHT	6,55 lbs
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	34,3 x 46,5 x 5,5 in



Ceiling lighting fixture for interiors, with direct and indirect light emission.

Pickled sheet metal ceiling bracket in polyacrylic paint.

Pickled sheet metal wall plate in polyacrylic paint.

Extruded aluminium structure in white, mat black, bronze, mat brass or titanium polyacrylic paint.

Joints in turned brass and die-cast aluminium in polyacrylic paint.


Die-cast aluminium end caps in polyacrylic paint.

Extruded polycarbonate diffusers with opaline finish.






Technical drawing



Polar diagram



<u>cd/klm</u> _____ co - c180 _ - - - c90 - c270