


PANZERI

Zero Round

120V-277V dimmable (0-10V)

P153U19.050.0453

 mat brass



Spec sheet

| | |
|--------------------------|----------------------------|
| CODE | P153U19.050.0453 |
| SYSTEM POWER CONSUMPTION | 29W |
| EFFICACY | 70.31lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L70 (B50) 60.000h |
| COLOUR TEMPERATURE | 3000K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | 120V-277V dimmable (0-10V) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 2835lm |
| DELIVERED LUMEN OUTPUT | 2039lm |
| EFFICIENCY | 71.9% |
| WEIGHT | 1,41 Kg |
| PROTECTION DEGREE | IP20 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS | 58,0 x 58,0 x 10,0 cm |



Ceiling or wall lighting fixture for interiors, with direct and indirect light emission.
Pickled sheet metal ceiling or wall bracket in polyacrylic paint.
Pickled sheet metal wall plate in polyacrylic paint.
Bended extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.
Extruded polycarbonate diffuser with opaline finish.

Technical drawing

Application



Polar diagram

