PANZERI

Firefly In The Sky

5V DC battery PE078U29.011.0514

Spec sheet

CODE	PE078U29.011.0514
SYSTEM POWER CONSUMPTION	2W
EFFICACY	67lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	5V DC
ELECTRICAL CONFIGURATION	battery
NOMINAL LUMINOUS FLUX	273lm
DELIVERED LUMEN OUTPUT	134lm
EFFICIENCY	49.1%
WEIGHT	0,91 Kg
PROTECTION DEGREE	IP65
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	14,0 x 63,0 x 12,5 cm





textured natural terracotta


DIRECT LIGHT

Floor lighting fixture for outdoor spaces, with direct light emission. Galvanized sheet metal peg for ground fixing in polyacrylic paint. Body in brass and aluminium in champagne, mat black, corten, bronze, textured olive green, textured soft white or textured natural terracotta polyacrylic paint. Removable head with magnetic fastening, in die-cast aluminium with polyacrylic paint. Silicone gaskets. Modelled acrylic diffuser with mat finish and serigraphy. Stainless steel screws. Push-button to adjust luminosity according to 5 levels of visual comfort. Battery status indicator integrated into the head. Feuipped with Li-Po hattery USB-C techargeable with up to 6 hours life at 100% of light

Equipped with Li-Po battery USB-C rechargeable, with up to 6 hours life at 100% of light emission and up to 24 hours life at 25%.

Equipped with battery charger with USB-C connector and adapter plug.

Polar diagram



Technical drawing

