PANZERI

Tubino

120V AC 120V ON-OFF

T073U06.002.0550





Spec sheet

CODE	T073U06.002.0550
SYSTEM POWER CONSUMPTION	13W
EFFICACY	52.15lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 80.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	adjustable
POWER SUPPLY	120V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	120V ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	950lm
DELIVERED LUMEN OUTPUT	678lm
EFFICIENCY	71.4%
WEIGHT	4,49 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	34,0 x 176,0 x 34,0 cm

Floor lighting fixture for interiors, with swivelling light beam. Turned pickled sheet metal bearing base in polyacrylic paint. Body in steel tube in white or mat black polyacrylic paint.

Turned brass joints in polyacrylic paint.

Turned aluminium structures in polyacrylic paint.

Turned aluminium swivelling heads in polyacrylic paint.

 $\label{thm:modelled} \mbox{Modelled polycarbonate diffusers with opaline finish.}$


Turned brass end caps in polyacrylic paint.

Equipped with connection cable between the heads and the body in transparent PVC. Equipped with a 2.5m (98.4") long power cable in transparent PVC with switch and plug.





Technical drawing







Polar diagram

