PANZERI

Hilow Line

120-277V AC dimmer on cable

T107U06.200.0522





Spec sheet

CODE	T107U06.200.0522
SYSTEM POWER CONSUMPTION	39W
EFFICACY	69.59lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B10) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	120-277V AC
FREQUENCY	60Hz
ELECTRICAL CONFIGURATION	dimmer on cable
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	4032lm
DELIVERED LUMEN OUTPUT	2714lm
EFFICIENCY	67.3%
WEIGHT	22,06 lbs
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 in



Floor lighting fixture for interiors, with indirect light emission.

Bearing base in "verde alpi" marble.

Extruded aluminium structure in mat black, bronze or mat brass polyacrylic paint.

Die-cast aluminium end caps in polyacrylic paint.

Extruded polycarbonate diffuser with opaline finish.

Equipped with a 3m (118,1") long power cable with switch to adjust luminosity and plug.







Technical drawing





Polar diagram

