# **PANZERI**

### Hilow Line

120V AC dimmer on cable

T109U17.200.0522





#### Spec sheet

CODE	T109U17.200.0522
SYSTEM POWER CONSUMPTION	39W
EFFICACY	69.59lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B10) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	120V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmer on cable
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	4032lm
DELIVERED LUMEN OUTPUT	2714lm
EFFICIENCY	67.3%
WEIGHT	10,01 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm

Floor lighting fixture for interiors, with indirect light emission.

Bearing base in black marquina marble.

 ${\bf Extruded\ aluminium\ structure\ in\ mat\ black,\ bronze\ or\ mat\ brass\ polyacrylic\ paint.}$ 

Die-cast aluminium end caps in polyacrylic paint.


Extruded polycarbonate diffuser with opaline finish.

Equipped with a 3m (118,1") long power cable with switch to adjust luminosity and plug.






## Technical drawing





## Polar diagram



cd/klm C0 - C180 - - - C90 - C270