


PANZERI

Murané


120V AC 120V ON-OFF
X115U05.010.0550

 champagne



Spec sheet

| | |
|--------------------------|--------------------|
| CODE | X115U05.010.0550 |
| SYSTEM POWER CONSUMPTION | 4W |
| EFFICACY | 41.75lm/W |
| LIGHT SOURCE | LED |
| COLOUR TEMPERATURE | 2700K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 120V AC |
| FREQUENCY | 60Hz |
| ELECTRICAL CONFIGURATION | 120V ON-OFF |
| DRIVER | remote included |
| DELIVERED LUMEN OUTPUT | 167lm |
| WEIGHT | 0,93 lbs |
| PROTECTION DEGREE | IP20 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS | 4,7 x 9,5 x 5,1 in |



Lighting fixture for ceiling or wall semi-built-in installation for interiors, with direct light emission.

Pickled sheet metal fixing bracket in white polyacrylic paint.

Built-in ceiling plate for permanent false ceilings, in pickled sheet metal in champagne polyacrylic paint.

Turned brass wiring support.

Diffuser in blown glass with bronze colour.


Turned aluminium closing disk in champagne polyacrylic paint.

Stainless steel spring clips for false ceiling fixing.

Equipped with 0,2m (7,9") long power cable.

Built-in hole dimension: \varnothing 70mm (\varnothing 2,8")

Technical drawing



Application



Polar diagram

