Corner

24V DC

XG2045-300TRACK





Spec sheet

CODE	XG2045-300TRACK
SYSTEM POWER CONSUMPTION	max 24W/m
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
GLARE RATING	UGR < 19
WEIGHT	4,51 lbs
PROTECTION DEGREE	IP40 IP20
PACKING DIMENSIONS	3,2 x 3,2 x 123,6 in
L (mm)	3010
L (in)	118 3/5"









Modular profile for ceiling or wall perimeter installation for interiors, with direct light

 $\label{eq:hidden} \mbox{Hidden structure for plasterboard panels, in extruded aluminium in RAL~9003~white}$ powder paint.

Extruded polycarbonate diffuser with opaline finish.

Light modules and driver to be ordered separately.

Fastening, joining and closing accessories to be ordered separately.


Technical drawing



Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270

Corner

Accessories / source		
XM006.012.0410	LED module, 125mm (5") 16 LED 2,2W 24V DC 3000K Ra>90 285lm.	
XM006.050.0410	LED module, 500mm (19,7") 64 LED 8,6W 24V DC 3000K Ra>90 1140lm.	
YLR005.010.0510	LED STRIP: 5m /5cm 9.6W/m 2700K CRI90 24V 1100lm/m	
YLR005.010.0610 C € [HL] 	LED STRIP: 5m /5cm 9.6W/m 4000K CRI90 24V 1300lm/m	
YLR006.017.0410 C € [HL] (m)	LED STRIP: 5m /5cm 16.8W/m 3000K CRI90 24V 2070lm/m	
YLR006.017.0510 C € EHL (III)	LED STRIP: 5m /5cm 16.8W/m 2700K CRI90 24V 1900lm/m	
YLR006.017.0610 C € EHL (III)	LED STRIP: 5m /5cm 16.8W/m 4000K CRI90 24V 2220lm/m	
YLR007.022.0410 C € [FII] (LED STRIP: 5m /4.2cm 22W/m 3000K CRI90 24V 2700lm/m	
YLR007.022.0510 C € ERL (w)	LED STRIP: 5m /4.2cm 22W/m 2700K CRI90 24V 2490lm/m	

Corner

Accessories / source

YLR007.022.0610

LED STRIP: 5m /4.2cm 22W/m 4000K CRI90 24V 2750lm/m



Corner

Accessories / diffusion

XM2033/34/45/46-1200S

Extruded polycarbonate diffuser with opaline finish, 12000mm (472,4") long.



XM2033/34/45/46-600S

Extruded polycarbonate diffuser with opaline finish, 6000mm (236,2") long.



CE EHI 🕸





XM2033/34/45/46-900S

Extruded polycarbonate diffuser with opaline finish, 9000mm (354,3") long.







Corner

Accessories / junction

XM2045-ANG 3

C€ [HI ⓓ

Connection joint for two lines of modular profiles with internal perpendicular junction 90° , for perimetral installation.



XM2045-ANG 4

C€ EHI ŵ

Connection joint for two lines of modular profiles with external perpendicular junction 90°, for perimetral installation.



XM2045-U

Linear junction.





XM2045-U901

CE EHI 🕸

Connection joint for two lines of modular profiles with internal level junction $90\,^\circ$, for perimetral installation.



XM2045-U90 2

Connection joint for two lines of modular profiles with external level junction 90° , for perimetral installation.





Corner

Accessories / closing

XM2045-T

Pair of end caps with screws.





