### Corner

24V DC

XG2045-300TRACK





#### Spec sheet

CODE	XG2045-300TRACK
SYSTEM POWER CONSUMPTION	max 24W/m
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
GLARE RATING	UGR < 19
WEIGHT	4,51 lbs
PROTECTION DEGREE	IP40 IP20
PACKING DIMENSIONS	3,2 x 3,2 x 123,6 in
L (mm)	3010
L (in)	118 3/5"









Modular profile for ceiling or wall perimeter installation for interiors, with direct light

 $\label{eq:hidden} \mbox{Hidden structure for plasterboard panels, in extruded aluminium in RAL~9003~white}$ powder paint.

Extruded polycarbonate diffuser with opaline finish.

Light modules and driver to be ordered separately.

Fastening, joining and closing accessories to be ordered separately.


### **Technical drawing**



### **Application**



### Polar diagram



cd/klm C0 - C180 - - - C90 - C270

### Corner

### Accessories / source

XM006.012.0410

LED module, 125mm (5") 16 LED 2,2W 24V DC 3000K Ra>90 285lm.









XM006.050.0410

LED module, 500mm (19,7") 64 LED 8,6W 24V DC 3000K Ra>90 1140lm.









### Corner

#### Accessories / diffusion

XM2033/34/45/46-1200S

Extruded polycarbonate diffuser with opaline finish, 12000mm (472,4") long.



XM2033/34/45/46-600S

Extruded polycarbonate diffuser with opaline finish, 6000mm (236,2") long.



CE EHI 🕸





Extruded polycarbonate diffuser with opaline finish, 9000mm (354,3") long.







### Corner

#### Accessories / junction

Connection joint for two lines of modular profiles with internal perpendicular junction 90°, for perimetral installation.

CE FINE 

Connection joint for two lines of modular profiles with external perpendicular junction 90°, for perimetral installation.

CE FINE 

Connection joint for two lines of modular profiles with external perpendicular junction 90°, for perimetral installation.



Linear junction.







XM2045-U901

C € EHI ®

Connection joint for two lines of modular profiles with internal level junction  $90\,^{\circ}$  , for perimetral installation.



XM2045-U90 2

Connection joint for two lines of modular profiles with external level junction  $90^{\circ}$ , for perimetral installation.







### Corner

### Accessories / closing

XM2045-T

Pair of end caps with screws.





